



# Technical Data Sheet

Ecosorb® 206A & 606A

Page 1

Ecosorb® 606A and 206A liquid additives are designed to control the odors associated with liquid asphalt in the paving industry. Additionally, Ecosorb additives are functional in controlling odors associated with the use of used oil fuels.

OMI Industries [OMI] is the manufacturer of Ecosorb products. Although the industrial odor control market has evolved, OMI has maintained its philosophy of environmental and worker friendly products while avoiding odor masking.

In response to the asphalt market's desire to be a good neighbor, and interest in odor control additives, OMI has developed the Ecosorb asphalt additive line of odor control products that are easy to use, safe for the environment, and offering no detrimental impacts on the physical properties of the asphalt. When added directly into liquid asphalt cement, the products function primarily via odorous emission suppression mechanisms.

Generally speaking, Ecosorb 606A is applied when using neat binders without performance enhancement additives such as anti-strip. Ecosorb 206A is generally applied when such additives are included in the binder.

The Ecosorb family of asphalt odor control additives have been used and proven effective in preventing or reducing odors associated with the production of paving materials throughout North America, Europe, Australia, and Pacific Rim countries.

## FEATURES

- High Flash Point
- Pleasant citrus or floral odor
- All natural ingredients

## ADVANTAGES

- Not a flammable liquid
- No strong odor at addition to liquid asphalt
- No hazardous ingredients for personnel

## PHYSICAL PROPERTIES

	<b>Ecosorb 606A</b>	<b>Ecosorb 206A</b>
Flash Point:	Approx. 350° F	Approx. 340° F
Boiling Point:	Approx. 340° F	Approx. 340° F
Specific Gravity:	Approx. 0.88	Approx. 0.88
Appearance:	Clear yellow liquid	Clear yellow liquid
Odor:	Slight citrus or floral odor	Slight citrus or floral odor



# Technical Data Sheet

Ecosorb® 206A & 606A

Page 2

## HMIS CLASSIFICATION

Health: 0  
Flammability: 1  
Reactivity: 0  
Protective Equipment: B

## ALL INGREDIENTS CAN BE FOUND LISTED ON THE FOLLOWING CHEMICAL SUBSTANCE INVENTORIES:

United States: TSCA  
Canadian: DSL  
European: EINECS  
Australian: AICS

## ADDITION TO LIQUID ASPHALT

Ecosorb additive is added to liquid asphalt at a nominal rate of one gallon of Ecosorb additive for each 10,000 gallons of liquid asphalt cement. Dosage rates can vary dependent upon the contents of the binder.

Ecosorb additive may be added directly to the hot mix plant or terminal storage tanks; agitation or recirculation is recommended. For those facilities operating liquid asphalt transport tankers, Ecosorb additive can be added by hand prior to loading the binder and the loading operation will properly mix the material. For large scale and automated operations, Ecosorb additive can be blended with in line injectors.

## PACKAGING OPTIONS

Ecosorb additives are available in the following sizes:  
5 Gallon Pails  
55 Gallon Drums  
275 Gallon Containers

**Ecosorb® Remarkably effective. Surprisingly simple.**

**OMI**  
INDUSTRIES

One Corporate Drive, Suite 100  
Long Grove, IL 60047 USA  
Phone: 800.662.6367 Fax: 847.304.0989  
[www.omi-industries.com](http://www.omi-industries.com)