

OdorFan Systems

A Simple, Efficient, and Economical Delivery System for Ecosorb Odor Neutralizer







APPLICATIONS

- · Remediation sites
- · Large indoor areas
- · Outdoor application, close to source
- Temporary sites or projects
- Multiple isolated odor areas
- · And more

For general odor control, OdorFan systems help circulate an ultra-fine atomized mist of Ecosorb® onto odorous spaces. Concentrated Ecosorb is mixed with water and pumped into the fan's jet stream, blowing the mist over a wide area or pinpointed odor source.

OdorFan systems can be installed on pole mounts, ceilings, walls, or connected directly to Ecosorb drums. Their pivoting fogging head allows for easy adjustment or continuous oscillation. Portable systems can be moved and placed, as needed. Metering pumps, product supply lines, and water hoses can be added to give maximum control.

BENEFITS

- Easy install
- No vapor duct or tubing
- Large coverage area
- Nozzle-free centrifugal atomization
- Washdown TEAO motors
- · Quick relocation potential

| | OdorFan | | Portable ORSM | |
|-----------------------|---|--|--------------------------------|--|
| | Technical | | | |
| Dimensions | 37" x 32.5" x 26" | | 21" x 25.5" x 44" | |
| Power | 115/230V, 1 Phase, 60Hz, 8 Amps @ 120VAC | 115/230V, 1 Phase, 60Hz, 12 Amps @ 120VAC | 115V, 1 Phase, 60Hz, 8 Amps | |
| Blower Specs | 0.5 HP; 2730 CFM | 1 HP; 3260 CFM | 0.5 HP; 2730 CFM | |
| Liquid Delivery | 0 - 36 GPD | 0 - 48 GPD | 0 - 36 GPD | |
| | F eatures | | | |
| Product Capacity | Dependant on system integrated with | | 18 Gal | |
| Portability | Not Portable | | Wheelable | |
| Liquid Output | Variable | | Adjustable | |
| Liquid Feed System | Available Separately | | Included | |
| | Options | | | |
| Oscillation | ✓ | | | |
| Explosion Proof Motor | ✓ | | ✓ | |
| Mounts | Pole, Wall, or Ceiling | | | |

| | Remediation Stand | | | |
|-----------------------|---|--|--|--|
| | Tecl | Technical | | |
| Dimensions | 32" x 36" x 98" | | | |
| Power | 115/230V, 1 Phase, 60Hz, 9 Amps @ 120VAC | 115/230V, 1 Phase, 60Hz, 12 Amps @ 120VAC | | |
| Blower Specs | 0.5 HP; 2730 CFM | 1 HP; 3260 CFM | | |
| Liquid Delivery | 0 - 36 GPD | 0 - 48 GPD | | |
| | Features | | | |
| Product Capacity | 55 Gal (Dilution Drum) - Included | | | |
| Portability | Forklift or Crane | | | |
| Liquid Output | Adjustable | | | |
| Liquid Feed System | Included | | | |
| | Options | | | |
| Oscillation | ✓ | | | |
| Explosion Proof Motor | ✓ | | | |
| Mounts | Large Wide Aluminum Base (Included) | | | |